

Data Sheet

Mixing / Magnetic Stirrers



Mini MR standard IKAMAG®

The improvement of the magnetic stirrer. new: For stirring quantities up to 1.000 ml (H₂O)
new: Infinitely variable speed from 0 - 2.500 rpm
- White set-up plate suitable for observing color reactions

Accessories: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, RSE Stirring bar remover

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	1
Stirring quantity max. (H ₂ O) [l]	1
Motor rating input [W]	3
Motor rating output [W]	2
Speed display	none
Speed range [rpm]	0 - 2500
Stirring bar length max. [mm]	30
Set-up plate material	polyester
Set-up plate dimensions [mm]	115 x 115
Dimensions (W x H x D) [mm]	114 x 37 x 127
Weight [kg]	0.25
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	no
Analog output	no
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	3
DC Voltage [V=]	12
Current consumption [mA]	300
Ident. No.	0003674001

Quasar Instruments, LLC
4835 Centennial Blvd.
Colorado Springs, CO 80919

T. 877-535-8001 F. 719-574-2404 E. Sales@qi-us.com