

## Data Sheet

Mixing / Magnetic Stirrers



### lab disc white

Ultra-flat compact magnetic stirrer, guaranteed with modern magnet coil technology. Wear-free drive with no moving parts. To ensure better mixing, the lab disc can reverse direction of rotation automatically every 30 seconds.

- High IP protection class (IP 65)
- Set-up plate and casing made from chemically resistant materials
- Slip-proof, safe stand

Accessories: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs)

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H <sub>2</sub> O) [l]	0.8
Motor rating input [W]	5
Motor rating output [W]	3
Speed range [rpm]	15 - 1500
Stirring bar length max. [mm]	25
Set-up plate material	polyester
Set-up plate dimensions [mm]	Ø 100
Dimensions (W x H x D) [mm]	117 x 12 x 180
Weight [kg]	0.3
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 65
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	5
<b>Ident. No.</b>	<b>0003907500</b>

ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, RSE Stirring bar remover



**Quasar Instruments, LLC**  
**4835 Centennial Blvd.**  
**Colorado Springs, CO 80919**

**T. 877-535-8001 F. 719-574-2404 E. [Sales@qi-us.com](mailto:Sales@qi-us.com)**